



4555SE

Electric Slab Scissor Lift

- 51 ft. (15.7 m) Working Height
- Drives at Full 45 ft. (13.7 m) Platform Height
- 55 in. (1.4 m) Overall Width for Narrow Aisles and Doorways
- Direct Electric Drive for Extended Duty Cycle
- Zero Inside Turning Radius
- Fully Proportional Lift and Drive Controls
- Roll-Out Deck Extension with Incremental Lock Position
- Standard Swing Gate
- Leading Value Solution for 50 ft. (15.7 m) Working Height

Drives at Full
Height on 55"
(1.4 m) Wide Base



Standard Features

Work Area

Roll-Out Deck Extension with Incremental Locking Positions
 Standard Swing Gate
 Lanyard Attachments (4)

Performance

Direct Electric Drive
 Fully Proportional Drive and Lift Controls

Power

24v 300Ah DC Electric Power
 Battery Charge Indicator

Serviceability

Lubrication-Free Scissor Bearings
 Easy Maintenance Access to Mechanical and Electrical Components
 in a Slide-Out Tray
 Logically Grouped Components and Numbered Wiring for Easy Reference

Safety

Dedicated Compartment Protects Electrical and Hydraulic Components
 Emergency Shut-Off at Platform and Lower Controls
 Non-Skid Metal Deck Construction
 Descent Alarm
 Drive Speed Interlock
 Multi-Axis Tilt Sensor
 Scissor Maintenance Lock
 Multiple Disc Brakes

Other Features

Removable Upper Controls
 Voltage-Compensating Fully Automatic Battery Charger
 Fold-Down Guardrails
 Hour Meter
 Machine Tie Downs
 Non-Marking Tires
 All Motion Alarm
 Fork Lift Pockets

Optional Features

Flashing Beacon (Continuous)
 900W Inverter
 Second Year Extended Warranty



MEC Aerial Work Platforms

Tel: 559.842.1500 | 1401 S. Madera Avenue, Kerman, CA 93630 | USA
 Toll free: 1.877.MEC LIFT | 1.877.632.5438 | Fax: 559.842.1520
 Email: info@MECawp.com | www.MECawp.com

MEC® is a registered trademark of California Manufacturing & Engineering Co., LLC. 97017 DTD 0718

4555SE	U.S.	Metric
Heights		
Working Height*	51 ft.	15.7 m
Platform Height	45 ft.	13.7 m
Stowed Height (Top Guardrail)	102 in.	2.6 m
Stowed Height (Rails Folded)	79 in.	2.0 m
Stowed Height (Platform Floor)	58 in.	1.5 m
Guardrail Height	43.5 in.	1.1 m
Toeboard Height	6 in.	15 cm
Ground Clearance (Stowed)	4 in.	10 cm
Ground Clearance (Elevated)	.7 in	2 cm
Dimensions		
Length-Stowed (Overall)	112 in.	2.8 m
Length-Stowed (Ladder Removed)	104 in.	2.6 m
Chassis Width	55 in.	1.4 m
Platform Length (Extended)	139 in.	2.5 m
Platform Length (Retracted)	104 in.	2.6 m
Roll-Out Deck Length	35 in.	0.9 m
Platform Width	44 in.	1.1 m
Wheelbase	87 in.	2.2 m
Total Lift Capacity	500 lbs	227 kg
Personnel Capacity	2	
Roll-Out Deck Capacity	250 lbs	113 kg
Speed		
Raise/Lower Speed	88 s / 60 s	
Drive Speed (Stowed)	2.5 mph	4.0 km/h
Drive Speed (Elevated)	0.5 mph	0.8 km/h
Performance		
Gradeability	25%	
Turning Radius (Inside)	0 in.	0 m
Weight**	7,190 lbs.	3,260 kg
Power Source	24 v DC, 300Ah Battery Pack	
Controls	Proportional Drive & Lift Controls	
Tires	15 x 5 in.	38 x 13 cm

*Metric equivalent of working height adds 2m to platform height. U.S. adds 6 ft. to platform height.
 **Weight may vary with certain options or configurations.

Important - MEC scissor lifts must be on a hard level surface while elevated.

Warranty - MEC Aerial Work Platforms carry a one (1) year warranty on defective component parts and a five (5) year warranty on defective structural parts. This warranty applies to the original owner only. Consult your MEC dealer for warranty details.

Meets or exceeds the requirements of ANSI A92.6-2006 and CSA B354.2-01.

Specifications subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.

Distributed by:

